

## DECLARATION OF PERFORMANCE

Nro. 005. CPR. HL.

**1. Unique identification code of the product-type:**

Kerabit Ridge Shingle  
Kerabit Eaves/ Ridge Shingle Easy

**2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

Dimensions	Color	Ridge shingle	Eaves/ Ridge shingle Easy
Ridge: 333 x 333 mm	Red	19410	50050
	Green	19411	50051
Eave: 333 x 1000 mm	Grey	19412	50052
	Brown	19413	50053
	Black	19414	50054
	Red/Black	19418	50068
	Green/Black	19415	
	White/Grey	19417	
	Brown/Black	19419	50069
	Copper	19461	
	Redmix	19420	
	Graphite	19422	
Brownmix	19424		

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Elastomer bitumen roofing shingles for roofs

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

Kerabit Oy  
Puistokatu 25- 27, 08150 Lohja, Finland  
P. 010 851 1000  
www.kerabit.fi

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

AVCP 3

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

The notified testing laboratory Eurofins Expert Services Oy, No. 0809 has carried out the determination of the product type on the basis of type-testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product

## 9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Tensile strength (width)	≥ 600 N/50 mm	EN 544: 2011
Tensile strength (height)	≥ 400 N/50 mm	
Nail shank tear resistance in the direction of height	≥ 100 N	
External fire performance	B <sub>ROOF</sub> (t2)	
Reaction to fire	Class E	
Mass of bitumen	≥1300 g/m <sup>2</sup>	
Dimensional variation		
- width (ridge)	333 mm, ± 3	
- width (eave)	1000 mm, ± 3	
- height	333 mm, ± 3	
Resistance to UV- radiation	pass	
Flow resistance at elevated temperature, 90 °C	≤ 2 mm	
Adhesion of granules	≤ 2,5 g	
Water absorption	≤ 2 %	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Lohja 8.6.2023



Veijo Kangasmaa  
Development and Quality Manager  
Kerabit Oy